



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Swiss Confederation

Federal Department of the Environment,
Transport, Energy and Communications DETEC

Federal Office for the Environment FOEN
Air Pollution Control and Chemicals Division

New instruments for PN-based periodic control: Results of a first measurement campaign

25.06.2014, ETH-Conference
Simone Krähenbühl, FOEN




Overview

- Swiss Regulation
- PN-based periodic control of construction machines
 - Measuring procedure
 - Reference value
- Measurement campaign
 - Results
 - Conclusions
- Work in Progress



Swiss Regulation

- The Swiss Ordinance on Air Pollution Control ([OAPC](#)) requires a limit value for particle number emission (1×10^{12} particles/kWh) for non-road mobile machinery (NRMM) used on construction sites.
→ this limit can only be met with diesel particulate filters (DPF).
- Periodic control of the machine every second year, done by the owner (Construction Guideline Air) .





PN-based periodic control of construction machines

- Current regulation for the periodic control of construction machines: opacimeter
→ ineffective for machines with particle filters.
Sensitivity of opacimeters is too low.
- FOEN and METAS defined requirements for «nanoparticle measuring instruments» in the existing Ordinance on Exhaust Measurement Instruments ([VAMV](#)).
- In 2012 instrument manufacturers were invited by METAS to develop instruments.
→ under construction

- official measurement procedure
- reference value



Measuring procedure for the official measurement

Conditioning of the engine and DPF:

- 4 to 6 free accelerations, until engine + DPF are warm
- Stay at maximum speed / high idle speed, until the engine is constant.

Measuring:

- Start measuring by pressing the button of your instrument.
- Read the result and compare with the reference value



Measurement, done by the instrument

Duration of the measurement: 40 seconds

- 15 sec waiting period
 - 5 sec measurement 1 → mean 1
 - 5 sec break
 - 5 sec measurement 2 → mean 2
 - 5 sec break
 - 5 sec measurement 3 → mean 3
- overall mean**



The reference value

Reference value of 2.5×10^5 particles/cm³
(analog to 1×10^{12} particles/kWh written in the OAPC)

- overall mean < reference value: **passed**
→ DPF and engine are in good condition.
- overall mean > reference value: **failed**
→ The problem has to be solved. Any use of the machine on a construction site is prohibited.





Measurement campaign

- Measurement campaign at AVESCO, Langenthal in April 2014
- Organization: FOEN, realisation and analysis: Laboratory for IC-Engines and Exhaust Gas Control, Biel
- 3 day-campaign, 15 measurements at construction machines, 4 measurements at stationary engines (compressors)
- 1 reference instrument (CPC 3790 TSI)
- 4 prototype instruments
- Aims: Testing the reference value and the measurement procedure.



Measurement campaign



| construction machine | chassis number. | type of engine | cylinder capacity | power | emission level | working hours | DPF | notes |
|---------------------------|-------------------|--------------------|-------------------|-------|----------------|---------------|-----------|------------|
| [-] | [-] | [-] | [lt] | [kW] | [-] | [hours] | [-] | |
| Caterpillar 305E | CAT0305ECXFA03375 | C2.4 | 2.4 | 31.2 | IIIA | 4.1 | Dinex | |
| Caterpillar TH414C | YC5A1789CKEK00298 | C3.4B | 3.4 | 75 | IIIA | 15 | OEM | |
| Caterpillar 308E2 | CAT0308ELTMX00810 | C3.3BT | 3.3 | 49 | IIIA | 6.9 | OEM | |
| Caterpillar M313D | CATM313DCK3D00240 | C4.4 | 4.4 | 102 | IIIB | 59 | OEM | |
| Caterpillar 908H | CAT0908HJLMD00476 | C3.4T | 3.3 | 59 | IIIA | 2291 | HJS | |
| Caterpillar 259B | CAT0259BKYYZ00955 | C3.4 | 3.4 | 55 | IIIB | 354 | Mobiclean | |
| Caterpillar CC34 | CAT0CC34C34600176 | C2.2 | 2.2 | 34.1 | IIIA | 1462 | HJS | |
| Caterpillar CS56 | CAT0CS56CFCS00489 | C6.6 | 6.6 | 108 | IIIA | 1311 | HJS | 3 x |
| Caterpillar 303C | CAT0303JBXT04518 | S3Q2-Y3SCM | 1.9 | 23.2 | IIIA | 2501 | HJS | DPF broken |
| Caterpillar 308C | CAT0308CEKCX01901 | 4M40-E1 | 2.835 | 40.5 | II | 5682 | HJS | |
| Kaeser M200 | WKA0F3500D4929321 | CAT. C6.6 | 6.6 | 205 | IIIA | 3 | Dinex | |
| Kaeser M43 | WKA0F085162343073 | Kubota V1505-T | 1.5 | 33 | II | 1007 | HJS | DPF broken |
| Kaeser M45-G | WKA0F1200E4985793 | Kubota V2203-M | 2.197 | 34 | IIIA | 1.4 | HJS | 2x |
| Thwaites Mach 474 | SLCM474Z1309C5145 | Yanmar 4TNV88-XWA2 | 2.19 | 33.3 | IIIA | 5.9 | Dinex | |
| Thwaites Mach 474 w/o DPF | SLCM474Z1409C7418 | Yanmar 4TNV88-XWA2 | 2.19 | 33.3 | IIIA | 1.1 | - | |
| Thwaites Mach 580 | SLCM580Z1306C5895 | Yanmar 3TNV88-XWA2 | 1.642 | 24.8 | IIIA | 2.3 | Dinex | |





Results (1/3)

Caterpillar 305E CR



CPC




Measurement instruments (prototypes)



Results (2/3)





Thwaites Mach 474
- with DPF
- without DPF



CPC


concentration [#/cm³]






Results (3/3)


Caterpillar CS56



Caterpillar 308C



Caterpillar 308E2





Conclusion of the measurement campaign

- The reference value of 2.5×10^5 particles/cm³ was well suited to make a distinction between good working and faulty DPF.
- The measuring procedure was appropriate, no problems appeared.
- The particle number emissions decreased over time
→ conditioning of the engine + DPF
- It was no problem for the engines to stay at maximum speed for about 15 minutes.



Work in Progress:

- An addition of the Construction Guideline Air with the measurement procedure and the reference value is planned.
 - For the periodic inspections of construction machines by the operator the new type of particle counters shall replace the opacimeters after a transition period.
- Switzerland's PN-based periodic control as a model for other applications with PN-limits.



Thanks

- to **Pierre Comte**,
Bern University of Applied Sciences, Laboratory for
IC-Engines and Exhaust Gas Control, Biel.
- to **Ruedi Ammann** and **Peter Baumann**,
AVESCO Langenthal.
- to the contributors of the prototype instruments.



In case of questions:

Simone Krähenbühl

Scientific Officer

Federal Office for the Environment FOEN

Air Pollution Control and Chemicals Division

Traffic Section

E-Mail: simone.kraehenbuehl@bafu.admin.ch

Phone: +41 58 465 31 86

